

The listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A computing device, comprising:
a housing, **the housing having an outer surface at least a portion of which is illuminable by light transmitted through an inner surface of the housing**, wherein the housing encloses at least various internal components associated with the operation of the computing device; and
an indicator assembly, wherein the indicator assembly indicates at least events associated with the computing device and produces at least a shaped indicator image at a specific small ~~region portion~~ of **the illuminable portion of the** ~~[[an]]~~ outer surface ~~of a housing component that forms an extended outer surface~~ of the housing when activated, and **eliminates to eliminate** the indicator image from the ~~extended~~ outer surface of the housing when deactivated, **and wherein the indicator assembly is not visible from outside the outer surface of the housing at least when deactivated**, the indicator assembly including
at least one light source capable of emitting light, and
a light guide that directs light emitted from the at least one light source so as to illuminate ~~a~~ ~~[[the]]~~ small ~~region portion~~ of **an inner surface of the housing adjacent the specific small region of the outer surface of** the housing ~~component~~ in order to create the shaped indicator image at the **specific small region of the** ~~extended~~ outer surface of the housing, the area of the shaped indicator image being substantially smaller than the area of the extended surface.
2. (Cancelled)
3. (Previously Presented) The computing device as recited in claim 1 wherein the light source includes an LED or a group of LEDs.
4. (Original) The computing device as recited in claim 3 wherein the light source includes a red, green, blue and white LED, the colored LEDs performing color mixing in order to effect the color of the indicator image.

5. (Previously Presented) The computing device as recited in claim 1 wherein the light is made incident on a translucent portion of the housing, the translucent portion transmitting light without permitting objects disposed behind it from being distinctly seen.
6. (Previously Presented) The computing device as recited in claim 1 wherein the indicator assembly further includes a mask that blocks light from illuminating all but the specific portion of the housing desired to be illuminated.
7. (Previously Presented) The computing device as recited in claim 1 wherein the light guide includes a light pipe for directing light to the part of the housing desired to be illuminated.
- 8-36. (Cancelled)
37. (Currently Amended) A computing device, comprising:
a housing component that forms an extended outer surface of a housing of the computing device, **the housing component having an outer surface at least a portion of which is illuminable by light transmitted through an inner surface of the housing component**; and
an indicator that alerts a user to a particular status of the computing device, the indicator including a light source and a light guide both of which are hidden from view **from outside the housing** and disposed inside the housing of the computing device, the light source when activated emits light into the light guide, the light guide directs the light emitted from the light source so as to illuminate a small **region of the inner surface** ~~portion~~ of the housing component in order to create a shaped indicator image at **a specific small region of the illuminable portion of the outer surface of the housing component adjacent the small region of the inner surface** ~~the extended outer surface of the housing~~, the area of the shaped indicator image being substantially smaller than the area of the extended **outer** surface **of the housing**.
38. (Previously Presented) The computing device as recited in claim 37 wherein the extended surface forms substantially the entire front surface of the housing of the computing device.
39. (Previously Presented) The computing device as recited in claim 37 wherein the shaped indicator image is a circle.

40. (Currently Amended) The computing device as recited in claim 37 wherein only the specific small region portion of the outer surface of the housing component is capable of being illuminated when light is made incident on an inner surface of the housing component.

41. (Currently Amended) The computing device as recited in claim 40 wherein the specific small region portion of the housing component is made illuminable via a recess formed in the inside surface of the housing component, the shape of the recess forming the shape of the shaped indicator image.

42. (Previously Presented) The computing device as recited in claim 1, wherein the light source is a remote light source.

43. (New) The computing device as recited in claim 1, wherein the indicator assembly is configured to turn the shaped indicator image on and off or cycle the shaped indicator image with increasing or decreasing intensity when in a sleep mode of the computing device.

44. (New) The computing device as recited in claim 37, wherein the indicator assembly is configured to turn the shaped indicator image on and off or cycle the shaped indicator image with increasing or decreasing intensity when in a sleep mode of the computing device.

45. (New) A computing device, comprising:

a housing that serves to surround internal components associated with the operation of the computing device at a peripheral region thereof so as to cover and protect the internal components from adverse conditions,

an indicator disposed internal of the housing and configured to illuminate a specific small portion of an external surface of the housing to form a shaped indicator image associated with an event of the computing device, the indicator image appearing on the external surface of the housing when the indicator is on, the indicator image disappearing from the external surface of the housing when the indicator is off, wherein the indicator image is only formed at the external surface of the housing when the indicator is turned on, wherein only the housing is visible and there is no trace of the indicator on the external surface of the housing when the indicator is off, and wherein the indicator does not form substantial breaks, lines, pits, and protrusions in the external surface of the housing.

46. (New) The computing device as recited in claim 45, wherein the translucency of the housing is configured to allow the passage of light therethrough while preventing a user from clearly seeing or distinguishing objects disposed within the housing.
47. (New) The computing device as recited in claim 45, wherein the housing transmits light while causing sufficient diffusion to prevent perception of distinct objects located within the housing.
48. (New) The computing device as recited in claim 47, wherein the housing includes a light diffusing means located either internal or external to the housing.
49. (New) The computing device as recited in claim 45, wherein an event of the computing device can be a computing device status condition or computing device status change.
50. (New) The computing device as recited in claim 45, wherein the indicator comprises at least one light source and at least one light guide, the light guide being arranged to guide light emitted from the light source to a portion of an inner surface of the housing adjacent and associated with the specific small portion of the external surface of the housing at which the shaped indicator image is illuminated.